

Report No.:WIFI PAR36 60DEG

Test Time: 2023-07-21 10:49

## Luminaire Property

Luminaire Manufacturer:

Voltage: 11.9 V

Power: 5.39 W

Current: 0.648 A

Power Factor: 0.701

## Photometric Results

CIE Class: Direct

Measurement Flux: 313.4 lm

Downward Ratio: 100%

Horizontal Diffuse Angle(25%,50%): H67.8,H49.5

Vertical Diffuse Angle(25%,50%): V67.1,V49.2

Luminaire Efficacy Rating (LER): 58.20

Max. Intensity: 392.43 cd

S/MH(C0/C180): 0.76

Total Rated Lamp Lumens: 313.4 lm

Efficiency: 100%


Upward Ratio: 0%

Central Intensity: 382.19 cd


Pos of Max. Intensity: H90 V5

S/MH(C90/C270): 0.77

Picture Of Luminaire



Luminous Intensity Distribution Curve



Unit: cd

Average Diffuse Angle(50%): 49.1°

— C0-C180 — C90-C270

C Plane (°):0.0-360.0: 45.0

Test Lab:

Test Type: TYPE C

Temperature: 22

Operator: liHong

Gamma Plane (°):0.0-90.0:1.0



Test Device: GPM-1600L

Distance: 9.260 m

Humidity:

Inspector:

## Luminous Intensity Distribution Curve



C Plane (°):0.0-360.0: 45.0

Test Lab:

Test Type: TYPE C

Temperature: 22

Operator: liHong

Gamma Plane (°):0.0-90.0:1.0


Test Device: GPM-1600L

Distance: 9.260 m

Humidity:

Inspector:

## Luminous Intensity Distribution Curve(cd/klm)



C Plane (°):0.0-360.0: 45.0

Test Lab:

Test Type: TYPE C

Temperature: 22

Operator: liHong

Gamma Plane (°):0.0-90.0:1.0


Test Device: GPM-1600L

Distance: 9.260 m

Humidity:

Inspector:

## Isocandela (rectangle)



Imax (100%): 392 cd

( 10%):	39 cd	( 16%):	63 cd
( 25%):	98 cd	( 40%):	157 cd
( 63%):	247 cd	(100%):	392 cd

C Plane (°):0.0-360.0: 45.0

Test Lab:

Test Type: TYPE C

Temperature: 22

Operator: liHong

Gamma Plane (°):0.0-90.0:1.0


Test Device: GPM-1600L

Distance: 9.260 m

Humidity:

Inspector:

## Isocandela (sphere)



Imax (100%): 392 cd

( 10%): 39 cd  
( 25%): 98 cd  
( 63%): 247 cd

( 16%): 63 cd  
( 40%): 157 cd  
(100%): 392 cd

C Plane (°):0.0-360.0: 45.0

Test Lab:

Test Type: TYPE C

Temperature: 22

Operator: liHong

Gamma Plane (°):0.0-90.0:1.0


Test Device: GPM-1600L

Distance: 9.260 m

Humidity:

Inspector:

## IsoLux Plot



Mounting Height: 10.0m Max Lux(100%): 3.9 lx

( 1%): 0.0 lx	( 2%): 0.1 lx
( 5%): 0.2 lx	( 10%): 0.4 lx
( 20%): 0.8 lx	( 50%): 1.9 lx
(100%): 3.9 lx	

C Plane (°):0.0-360.0: 45.0

Test Lab:

Test Type: TYPE C

Temperature: 22

Operator: liHong

Gamma Plane (°):0.0-90.0:1.0

Test Device: GPM-1600L

Distance: 9.260 m



Humidity:

Inspector:

## Lum Limit Curve

Dazzle	Quality	Illuminance (lx)							
1.15	A	2000	1000	500	<=300				
1.50	B		2000	1000	500	<=300			
1.85	C			2000	1000	500	<=300		
2.20	D				2000	1000	500	<=300	
2.55	E					2000	1000	500	<=300

a b c d e f g h



L(cd/sq.m)	G45	G50	G55	G60	G65	G70	G75	G80	G85
C0	41	26	17	11	8	5	3	1	0
C90	50	31	20	13	8	5	3	2	0
C180	28	19	12	8	5	3	2	0	0
C270	23	15	11	7	5	3	1	0	0

C Plane (°):0.0-360.0: 45.0

Test Lab:

Test Type: TYPE C

Temperature: 22

Operator: liHong

Gamma Plane (°):0.0-90.0:1.0


Test Device: GPM-1600L

Distance: 9.260 m

Humidity:

Inspector:

## Illuminance at a Distance





## UGR Table


Reflectance:										
Ceiling (cavity)	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
X=2H Y=2H	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$
3H	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$
4H	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$
6H	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$
8H	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$
12H	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$
X=4H Y=2H	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$
3H	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$
4H	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$
6H	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$
8H	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$
12H	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$
X=8H Y=4H	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$
6H	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$
8H	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$
12H	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$
X=12H Y=4H	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$
6H	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$
8H	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$	-1.\$
Variations with the observer position at spacings:										
S=1.0H	-1.\$/-1.\$					-1.\$/-1.\$				
S=1.5H	-1.\$/-1.\$					-1.\$/-1.\$				
S=2.0H	-1.\$/-1.\$					-1.\$/-1.\$				

Calculate in accordance with CIE Pub.117. The table is revised with  $313\text{lm}$  ( $8\log(F/F_0) = -4.0$ ).

C Plane (°):0.0-360.0: 45.0  
Test Lab:  
Test Type: TYPE C  
Temperature: 22  
Operator: liHong

Gamma Plane (°):0.0-90.0:1.0  
Test Device: GPM-1600L  
Distance: 9.260 m  
Humidity:  
Inspector:

**FLUX DISTRIBUTION TABLE BASED ON THE IESNA LUMINAIRE CLASSIFICATION SYSTEM**



ZONE	LUMENS	% LAMP LUMENS
FORWARD LIGHT	178	56.9
FL ( 0°-30°)	113	36.0
FM (30°-60°)	60	19.1
FH (60°-80°)	5	1.7
FVH (80°-90°)	0	0.1
BACK LIGHT	135	43.1
BL ( 0°-30°)	92	29.2
BM (30°-60°)	40	12.7
BH (60°-80°)	4	1.2
BVH (80°-90°)	0	0.0
UP LIGHT	0	0.0
UL (90°-100°)	0	0.0
UH (100°-180°)	0	0.0
TRAPPED LIGHT	NA	NA

BUG(Backlight,Uplight,Glare) Rating Base On TM-15-07	
Asymmetrical Luminaire Types (Type I,II,III,IV)	B0 U0 G0
Quadrilateral Symmetrical Luminaire Types (Type V,Area Light)	B0 U0 G0

C Plane (°):0.0-360.0: 45.0  
 Test Lab:  
 Test Type: TYPE C  
 Temperature: 22  
 Operator: liHong

Gamma Plane (°):0.0-90.0:1.0  
 Test Device: GPM-1600L  
 Distance: 9.260 m  
 Humidity:  
 Inspector:

## Zonal Lumen

Gamma [°]	I <sub>mean</sub> [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
0.0-1.0	382.0	0.4	0.4	0.12	0.12
1.0-2.0	381.1	1.1	1.5	0.35	0.47
2.0-3.0	379.5	1.8	3.3	0.58	1.04
3.0-4.0	377.0	2.5	5.8	0.81	1.85
4.0-5.0	373.9	3.2	9.0	1.03	2.88
5.0-6.0	369.8	3.9	12.9	1.24	4.12
6.0-7.0	365.1	4.5	17.4	1.45	5.56
7.0-8.0	359.7	5.1	22.6	1.64	7.21
8.0-9.0	353.5	5.7	28.3	1.83	9.03
9.0-10.0	346.9	6.3	34.6	2.00	11.04
10.0-11.0	339.5	6.8	41.4	2.16	13.20
11.0-12.0	331.4	7.2	48.6	2.31	15.51
12.0-13.0	323.1	7.7	56.3	2.45	17.96
13.0-14.0	314.0	8.0	64.3	2.56	20.52
14.0-15.0	304.7	8.4	72.7	2.67	23.19
15.0-16.0	295.0	8.6	81.3	2.76	25.95
16.0-17.0	284.7	8.9	90.2	2.83	28.78
17.0-18.0	274.4	9.0	99.3	2.89	31.67
18.0-19.0	263.5	9.2	108.4	2.93	34.59
19.0-20.0	252.5	9.2	117.7	2.95	37.54
20.0-21.0	241.6	9.3	126.9	2.96	40.50
21.0-22.0	230.2	9.3	136.2	2.95	43.45
22.0-23.0	218.8	9.2	145.4	2.93	46.38
23.0-24.0	207.5	9.1	154.4	2.89	49.28
24.0-25.0	196.0	8.9	163.4	2.84	52.12
25.0-26.0	185.0	8.7	172.1	2.79	54.91
26.0-27.0	173.7	8.5	180.6	2.71	57.62
27.0-28.0	162.7	8.2	188.8	2.63	60.25
28.0-29.0	152.1	8.0	196.8	2.54	62.79
29.0-30.0	141.5	7.6	204.4	2.44	65.22
30.0-31.0	131.5	7.3	211.8	2.33	67.56
31.0-32.0	121.8	7.0	218.7	2.23	69.79
32.0-33.0	112.3	6.6	225.3	2.11	71.90
33.0-34.0	103.6	6.3	231.6	2.00	73.90
34.0-35.0	95.1	5.9	237.5	1.88	75.78
35.0-36.0	87.1	5.5	243.1	1.77	77.55

C Plane (°):0.0-360.0: 45.0  
 Test Lab:  
 Test Type: TYPE C  
 Temperature: 22  
 Operator: liHong

Gamma Plane (°):0.0-90.0:1.0  
 Test Device: GPM-1600L  
 Distance: 9.260 m  
 Humidity:  
 Inspector:

**Zonal Lumen (Continue 1)**

Gamma [°]	I <sub>mean</sub> [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
36.0-37.0	79.7	5.2	248.3	1.66	79.21
37.0-38.0	72.7	4.9	253.1	1.55	80.76
38.0-39.0	66.2	4.5	257.6	1.44	82.20
39.0-40.0	60.3	4.2	261.9	1.34	83.54
40.0-41.0	54.8	3.9	265.8	1.25	84.79
41.0-42.0	49.9	3.6	269.4	1.16	85.95
42.0-43.0	45.4	3.4	272.7	1.07	87.02
43.0-44.0	41.3	3.1	275.9	0.99	88.01
44.0-45.0	37.6	2.9	278.8	0.92	88.94
45.0-46.0	34.3	2.7	281.4	0.85	89.79
46.0-47.0	31.3	2.5	283.9	0.79	90.59
47.0-48.0	28.5	2.3	286.2	0.74	91.32
48.0-49.0	26.0	2.1	288.4	0.68	92.01
49.0-50.0	23.9	2.0	290.4	0.64	92.64
50.0-51.0	21.9	1.8	292.2	0.59	93.23
51.0-52.0	20.0	1.7	293.9	0.55	93.78
52.0-53.0	18.4	1.6	295.5	0.51	94.29
53.0-54.0	16.9	1.5	297.0	0.47	94.76
54.0-55.0	15.5	1.4	298.4	0.44	95.21
55.0-56.0	14.3	1.3	299.7	0.41	95.62
56.0-57.0	13.1	1.2	300.9	0.38	96.00
57.0-58.0	12.1	1.1	302.0	0.36	96.36
58.0-59.0	11.2	1.0	303.1	0.33	96.69
59.0-60.0	10.3	1.0	304.0	0.31	97.00
60.0-61.0	9.5	0.9	304.9	0.29	97.29
61.0-62.0	8.7	0.8	305.8	0.27	97.56
62.0-63.0	8.1	0.8	306.6	0.25	97.81
63.0-64.0	7.4	0.7	307.3	0.23	98.04
64.0-65.0	6.8	0.7	308.0	0.21	98.26
65.0-66.0	6.2	0.6	308.6	0.20	98.46
66.0-67.0	5.7	0.6	309.2	0.18	98.64
67.0-68.0	5.2	0.5	309.7	0.17	98.81
68.0-69.0	4.7	0.5	310.2	0.15	98.96
69.0-70.0	4.3	0.4	310.6	0.14	99.10
70.0-71.0	3.9	0.4	311.0	0.13	99.23
71.0-72.0	3.5	0.4	311.4	0.12	99.35

C Plane (°):0.0-360.0: 45.0  
Test Lab:  
Test Type: TYPE C  
Temperature: 22  
Operator: liHong

Gamma Plane (°):0.0-90.0:1.0  
Test Device: GPM-1600L  
Distance: 9.260 m  
Humidity:  
Inspector:

## Zonal Lumen (Continue 2)

[illegible]

C Plane (°):0.0-360.0: 45.0  
Test Lab:  
Test Type: TYPE C  
Temperature: 22  
Operator: liHong

Gamma Plane (°):0.0-90.0:1.0  
Test Device: GPM-1600L  
Distance: 9.260 m  
Humidity:  
Inspector:

## Candlepower Table

Unit: cd

G\C	C0.0	C45.0	C90.0	C135.0	C180.0	C225.0	C270.0	C315.0	C360.0	
G0.0	382.2	382.2	382.2	382.2	382.2	382.2	382.2	382.2	382.2	
G1.0	382.1	385.0	386.2	383.2	381.4	378.1	377.6	380.2	382.1	
G2.0	381.2	387.0	388.9	383.5	379.8	373.9	372.6	377.4	381.2	
G3.0	379.4	388.5	391.1	382.8	377.1	368.2	366.3	373.7	379.4	
G4.0	377.1	389.0	392.2	381.3	373.6	362.6	359.8	369.8	377.1	
G5.0	373.8	388.7	392.4	379.2	369.1	356.4	352.2	364.8	373.8	
G6.0	369.6	387.5	391.7	375.9	364.0	348.5	344.4	359.0	369.6	
G7.0	365.0	385.5	390.4	371.9	358.5	341.0	336.4	352.9	365.0	
G8.0	359.6	382.4	388.0	367.0	351.4	332.1	326.8	346.0	359.6	
G9.0	353.4	378.5	384.6	361.5	344.6	323.1	317.8	339.2	353.4	
G10.0	346.7	374.2	380.7	355.6	336.7	313.9	307.9	331.7	346.7	
G11.0	339.4	368.7	375.5	348.3	327.8	303.4	297.1	323.5	339.4	
G12.0	331.8	362.7	369.8	341.2	318.9	293.0	286.3	315.2	331.8	
G13.0	324.1	356.3	363.9	333.1	308.3	282.3	274.9	307.1	324.1	
G14.0	315.0	348.5	356.2	324.1	298.7	270.9	263.6	297.5	315.0	
G15.0	306.6	341.2	348.9	314.9	288.1	259.3	252.7	288.6	306.6	
G16.0	297.9	332.3	340.8	305.0	276.6	247.0	240.7	278.7	297.9	
G17.0	287.7	323.6	331.3	294.8	265.2	235.6	228.9	269.0	287.7	
G18.0	278.6	314.8	322.2	284.2	254.1	223.4	217.1	259.5	278.6	
G19.0	267.9	304.9	311.5	272.8	240.9	210.7	204.7	248.7	267.9	
G20.0	258.0	295.0	301.8	262.0	229.3	199.1	193.4	238.4	258.0	
G21.0	248.4	285.4	291.1	251.1	216.3	187.1	181.0	228.6	248.4	
G22.0	237.3	274.2	279.6	238.3	204.0	174.1	169.5	217.1	237.3	
G23.0	227.6	264.2	268.3	226.5	192.2	163.1	158.6	206.5	227.6	
G24.0	217.8	252.5	256.7	214.1	179.0	150.6	146.5	195.3	217.8	
G25.0	206.4	241.8	244.2	202.2	167.7	139.9	136.4	185.0	206.4	
G26.0	196.0	230.9	232.7	190.3	156.1	129.7	126.1	174.1	196.0	
G27.0	185.0	219.5	219.6	177.9	144.1	119.0	115.8	162.8	185.0	
G28.0	174.7	208.4	207.6	166.2	133.3	109.3	106.5	152.6	174.7	
G29.0	164.3	197.9	196.0	154.7	122.2	100.3	97.2	142.1	164.3	
G30.0	153.7	186.1	183.2	143.1	112.6	91.5	88.9	131.0	153.7	
G31.0	143.5	175.7	171.8	132.4	103.6	83.7	81.5	121.6	143.5	
G32.0	133.5	164.1	160.3	121.2	94.0	76.1	74.1	111.2	133.5	
G33.0	123.3	153.5	148.5	111.9	86.3	69.5	67.9	102.3	123.3	
G34.0	113.7	143.2	137.5	102.6	78.7	63.6	62.0	94.0	113.7	
G35.0	104.1	132.5	126.4	93.1	71.5	57.7	56.1	85.0	104.1	
G36.0	95.4	122.6	116.3	85.4	65.2	52.6	51.3	77.7	95.4	

C Plane (°):0.0-360.0: 45.0

Test Lab:

Test Type: TYPE C

Temperature: 22

Operator: liHong

Gamma Plane (°):0.0-90.0:1.0

Test Device: GPM-1600L

Distance: 9.260 m

Humidity:

Inspector:

**Candlepower Table (Continue 1)**

Unit: cd

G\C	C0.0	C45.0	C90.0	C135.0	C180.0	C225.0	C270.0	C315.0	C360.0	
G37.0	87.3	113.4	106.7	77.8	59.1	48.0	46.5	70.6	87.3	
G38.0	79.0	103.4	97.3	70.1	53.8	43.6	42.5	63.6	79.0	
G39.0	72.4	94.7	88.9	64.1	49.2	39.8	39.0	58.0	72.4	
G40.0	65.9	86.1	81.0	58.0	44.5	36.2	35.5	52.1	65.9	
G41.0	59.5	78.5	73.1	52.8	40.8	33.2	32.5	47.2	59.5	
G42.0	54.4	71.5	66.7	48.0	37.3	30.5	30.0	43.1	54.4	
G43.0	49.0	64.7	60.0	43.3	33.9	27.8	27.3	38.9	49.0	
G44.0	44.8	58.8	54.7	39.5	31.1	25.6	25.2	35.4	44.8	
G45.0	40.9	53.2	49.6	35.7	28.4	23.5	23.1	32.4	40.9	
G46.0	37.2	48.2	44.9	32.7	26.0	21.6	21.3	29.3	37.2	
G47.0	34.0	44.0	40.9	29.8	24.0	20.0	19.7	26.9	34.0	
G48.0	30.8	39.7	36.9	27.1	21.9	18.3	18.2	24.5	30.8	
G49.0	28.2	36.2	33.7	24.8	20.3	16.9	16.8	22.4	28.2	
G50.0	25.8	33.1	30.8	22.7	18.5	15.7	15.4	20.6	25.8	
G51.0	23.6	30.0	27.9	20.7	17.1	14.4	14.3	18.9	23.6	
G52.0	21.7	27.4	25.5	19.1	15.8	13.3	13.3	17.3	21.7	
G53.0	20.0	24.9	23.3	17.3	14.5	12.3	12.3	15.9	20.0	
G54.0	18.4	22.9	21.3	16.0	13.4	11.3	11.4	14.8	18.4	
G55.0	16.9	21.0	19.5	14.8	12.4	10.5	10.6	13.6	16.9	
G56.0	15.5	19.2	17.9	13.5	11.4	9.7	9.8	12.5	15.5	
G57.0	14.4	17.7	16.4	12.4	10.5	9.0	9.1	11.5	14.4	
G58.0	13.3	16.3	15.1	11.5	9.6	8.3	8.4	10.7	13.3	
G59.0	12.3	15.0	13.8	10.5	8.9	7.7	7.7	9.8	12.3	
G60.0	11.4	13.8	12.7	9.7	8.1	7.1	7.2	9.1	11.4	
G61.0	10.5	12.7	11.8	8.9	7.5	6.5	6.6	8.4	10.5	
G62.0	9.7	11.7	10.8	8.2	6.9	6.0	6.1	7.7	9.7	
G63.0	9.0	10.8	9.9	7.5	6.4	5.5	5.6	7.2	9.0	
G64.0	8.2	9.9	9.1	6.9	5.8	5.0	5.1	6.6	8.2	
G65.0	7.7	9.1	8.4	6.4	5.3	4.5	4.7	6.0	7.7	
G66.0	7.0	8.4	7.7	5.8	4.8	4.1	4.2	5.6	7.0	
G67.0	6.4	7.7	7.1	5.3	4.4	3.7	3.8	5.1	6.4	
G68.0	5.9	7.1	6.5	4.9	4.0	3.3	3.5	4.6	5.9	
G69.0	5.4	6.5	6.0	4.4	3.6	2.9	3.1	4.2	5.4	
G70.0	4.9	6.0	5.4	4.0	3.2	2.6	2.8	3.8	4.9	
G71.0	4.5	5.5	5.0	3.6	2.9	2.3	2.5	3.4	4.5	
G72.0	4.0	5.0	4.5	3.2	2.5	2.0	2.1	3.1	4.0	
G73.0	3.6	4.5	4.1	2.9	2.2	1.7	1.9	2.7	3.6	

C Plane (°):0.0-360.0: 45.0

Test Lab:

Test Type: TYPE C

Temperature: 22

Operator: liHong

Gamma Plane (°):0.0-90.0:1.0

Test Device: GPM-1600L

Distance: 9.260 m

Humidity:

Inspector:

### Candlepower Table (Continue 2)

Unit: cd

[illegible]

C Plane (°):0.0-360.0: 45.0

Test Lab:

Test Type: TYPE C

Temperature: 22

Operator: liHong

Gamma Plane (°):0.0-90.0:1.0

Test Device: GPM-1600L

Distance: 9.260 m

Humidity:

Inspector: