

LOW VOLTAGE BISTRO STRING REEL

DESCRIPTION

The Brilliance Low Voltage Bistro String Reel comes in a 328 ft. spool (100m) and can be cut to length per your requirements. Use this low voltage bistro string with the corresponding low voltage string connection accessories for custom length bistro lighting. This string is for use with low voltage lamps only. Dimmable with Brilliance Dimmer and most magnetic transformers. Mounting cable and turnbuckles are not included. Connection accessories and lamps are sold separately.

LOW VOLTAGE BISTRO STRING REEL FEATURES

- Patented design (U.S. Patent D898986S)
- Uses 14 AWG cable and features a waterproof seal
- Two-way mounting holes at each lamp position eliminate the need for zip ties and creates a more secure installation for the life of the string lights

LOW VOLTAGE BISTRO STRING REEL SPECS

Operating Range	12VAC
Total Length	328 feet reel (100 meters) Can be cut to length
String Lead Length	At least 10 inches of lead required for connections
Distance Between Lamp Positions	24 inches between lamps
Includes	Low Voltage Bistro String (14 AWG)
Connection Accessories Available	Straight Connector: 1 per cable conversion T Connector: 1 per center feed End Cap: 1 per string end
Warranty (years)	2

S14 LAMP REQUIREMENTS

Lamp	1W, 12VAC	2W, 12VAC	3.5W, 12 VAC
Max. # of Lamps	75	50	30
Max. Wattage	125.25 with VA	117.5 with VA	117.9 with VA
Max. String Length	150 ft. end-to-end	100 ft. end-to-end	60 ft. end-to-end



Part Number:

LOW-VOLT-BISTRO-REEL

NEC® Article 411.5 (B): Lighting systems shall be installed not less than 3m (10ft.) horizontally from the nearest edge of the water, unless permitted by Article 680.



Two-way mounting holes

